Floover Loose Lay Antiskid flooring, size 1828,8x228,6x5,0 mm, Natural range, reference NT1203. Classification 23/33 with high abrasion resistance, stains resistance class 0 according to norm EN423, fire resistance classification BflS1 and grade 6 of UV resistance. It should be installed on a dry and perfectly levelled subfloor. Before installing, allow the material to acclimatize for 48 hours in the installation area. The installation should be made without glue, directly to the floor and without expansion joints. Temperature must be controlled between 18 and 27ºC before, during and after the installation.

LOOSE LAY ANTISKID

TECHNICAL DATA SHEET

Floover Loose Lay Antiskid consists of 4 layers. The top layer is a resistant transparent PVC . This adapts perfectly to the elasticity of the vinyl below creating a nice walking surface. The third layer is made with 100% PVC and fiberglass that gives a great comfort and stability. Finally it has a special antiskid underlayment that increases also the stability of the system. Available only in Natural collection

Only for Natural range

PHTHALATES FREE

A+ A B C

CE EN 14041

① Layer of transparent PVC 0,55 mm
② Printed Decor
③ Core layer PVC reinforced with fiberglass
④ Backing PVC with micro antiskid

Microbevel 4 sides

Suction pad system
ANTISKID underlayment

Characteristics	Test	Loose Lay Antiskid
Classification	EN 16511	23/33
Dimensions	EN 427	1828,8 x 228,6 mm
Thickness	EN 430	5 mm
Weight	EN 430	9,95 kg/m^2
Abrasion Resistance	EN 660-2: 99	≥ 0,015 gr/1000 r
Chemical Resistance	EN 438	Class 0
Fire Resistance	EN 13501-1	Class BFLs1 (B1)
Dimensional Stability	EN 434	- 0,12 %
Curving	EN 434	0,5 mm
Acoustic Certification	EN ISO 717-2	ΔLw= 15 dB
Cigarette burn resistance	EN 438 - 2	Class 3
Flexibility	EN 435	20 mm
Slip/Slide resistance	EN 13893	DS Grade
Formaldehyde emission	EN 717	E1
UV Resistance	ISO 105	≥ Grade 6
Castor Chair	EN 425	Suitable for type W
Antistatic Performance	EN 1815	< 2 kv
Residual Indentation	EN 433	max. 0,10 mm
Water Resistance	EN 317	0% Swelling

Slip Resistant | Fire Resistant | Ecological | Abrasion Resistant | Antistatic | Chemical Resistant | Silent | UV Ray Resistant | Impact Resistant | Waterproof